

## TRIOBALECOMPRESSOR ASSORTMENT

### PRODUCT TO MACHINE MATRIX

Dimension [mm x mm x m]	Colour	Machine	Pre Stretch Level
1280 x 0,013 x 3000	tinted white	Stationary: Göweil, Orkel, Flexus Balasystem	5 - 10 %
1280 x 0,017 x 2200	tinted white	Stationary: Göweil, Orkel Mobile: Krone Comprima	10 - 20 %
1350 x 0,020 x 1700	tinted white	Stationary: Göweil Mobile: Göweil, CNH, Agronic, Orkel	15 - 30 %
1400 x 0,017 x 2000	tinted white	Mobile: Göweil, CNH, Agronic, Orkel, McHale	18 - 30 %
1400 x 0,017 x 4200	tinted white	Stationary: Flexus Balasystem Mobile: McHale Fusion 3 Plus	18 - 30 %
1400 x 0,020 x 1750	tinted white	Mobile: Göweil, CNH, Agronic, Orkel, McHale	20 - 35 %



## *13 $\mu$ m – 1280 mm – 3000 m*

- Keeps the bale tight together but the film is still stretchable in the machine with 5-10%.
- Reel with 3000m for maximum output.
- Film goes from edge to edge.
- For stationary machines such as Göweil LT Master, Orkel MP 2000 and Flexus Bala system.
- Made for fresh maize crop and similar crops.

## *17 $\mu$ m – 1280 mm – 2200 m*

- Keeps the bale tight together but the film is still stretchable 10- 20%.
- Film goes from edge to edge.
- For usage with mobile and stationary balers.
- If customer wants a narrower film than 1400mm for mobile machines.
- For more demanding use than 13 $\mu$ m in stationary machines.

## *20 $\mu$ m – 1350 mm – 1700 m*

- For stationary machines there the customer wants to stretch the film hard on the bales to get a perfect bale shape and want to have a cover edge option.
- Also used for Mobile balers in Switzerland equipped with Swiss made NRF feeder.
- Product also used where we have limitation in the width of the reel holder.
- If customer wants a narrower film than 1400mm for mobile machines.

## *17 $\mu$ m – 1400 mm – 2000 m*

## *20 $\mu$ m – 1400 mm – 1750 m*

- For mobile balers with the option of stretch= more bales/reel or cover edge= less bales per reel (when conditions allow for it).
- For stationary machines that can use this width of reels.
- For Silage, haylage, beet pulp and other demanding crops.
- Made for demanding conditions.

## *17 $\mu$ m – 1400 mm – 4200 m*

- For the professional user of McHale Fusion 3 plus machines that wants to avoid lifting reels by hand and for minimal reel changes.
- Often used by customers that does most of the bales with net replacement film.
- Reel weight of 100kg demands a loader for lifting them on the machine.